

Antennas Field Generating Pvramidal Horn Pyramidal Model 3162-01

Features:

- 1.1 GHz to 1.5 GHz Frequency Range
- Generates 600 V/m with <500 W
- **Meets Specs for:** -- GMW 3097
 - -- ES-XW7T-1A278-AC



ETS-Lindgren's Model 3162-01 Field Generating Pyramidal Horn

ETS-Lindgren's EMCO Model 3162-01 Pyramidal Type High

Gain Horn was specifically developed for the GMW 3097 and ES-XW7T-1A278-AC specifications for automotive EMC components testing. These tests require that the EUT be exposed to a pulsed peak field level of 600 V/m at a distance of 100 cm from the front of the horn. Because of near field gain compression, most horns fail to meet this spec at the required test distance. The Model 3162-01 optimizes the near field behavior to overcome this problem, and

produces a field level of 600 V/m with a 500 W amplifier.


Technical Description


The Model 3162-01 horn aperture is 65 cm by 45 cm and has extended ground planes with chokes for better gain on each side.

Standard Configuration

- Pyramidal horn antenna with a coax to waveguide adapter
- Two-year warranty

Typical Test Setup





Chamber ground

Electrical Specifications


MODEL	FREQUENCY RANGE	VSWR RATIO	MAXIMUM CONTINUOUS INPUT POWER	INPUT IMPEDANCE	RF CONNECTORS
3162-01	1.1 GHz - 1.5 GHz	1.5:1 Typical	550 W	50 Ω	Female
		2:1 Maximum			Type N

Physical Specifications


		EL	LENGTH	WIDTH	HEIGHT	WEIGHT	
	3162	-01	160.27 cm 63.1 in	64.77 cm 25.5 in	74.68 cm 29.4 in	23.6 kg 52.0 lbs	
USA: Tel +1.512.531.	.6400	FINLAND: Tel +358.2.8383.300	UK: Tel +44.(0)1438.730700	FRANCE: Tel +33.1.48.65.34.03	CHINA: Tel +8610.8275.5086	JAPAN: Tel +81.3.3813.7100	ONLINE: info@ets-lindgren.con
Fax +1.512.531.		Fax +358.2.8651.233		Fax +33.1.48.65.43.69	Fax +8610.8275.5537	Fax +81.3.3813.8068	www.ets-lindgren.com







Antenna Input Power, Horizontal Polarization, With Test Points



ONLINE: FRANCE: CHINA: **JAPAN:** USA: **FINLAND:** UK: Tel +1.512.531.6400 Tel +358.2.8383.300 Tel +44.(0)1438.730700 Tel +33.1.48.65.34.03 Tel +8610.8275.5086 Tel +81.3.3813.7100 info@ets-lindgren.com Fax +1.512.531.6500 Fax +358.2.8651.233 Fax +44.(0)1438.730751 Fax +33.1.48.65.43.69 Fax +8610.8275.5537 Fax +81.3.3813.8068 www.ets-lindgren.com Information presented is subject to change as product enhancements are made. Contact ETS-Lindgren Sales Department for current specifications. 10/06 - PDF E © 2006 ETS-Lindgren REV C