

# Digital Phosphor Oscilloscopes

## MSO4000 Series, DPO4000 Series Data Sheet



### Ease of Use Features

- Wave Inspector® Controls Provide Unprecedented Efficiency in Waveform Analysis
- 10.4 in. (264 mm) XGA Color Display
- USB and CompactFlash on Front Panel for Quick and Easy Storage
- USB Plug-and-Play PC Connectivity
- Small Footprint and Lightweight – Only 5.4 in. (137 mm) deep and 11 lb. (5 kg)
- TekVPI® Probe Interface Supports Active, Differential, and Current Probes for Automatic Scaling and Units

### Serial Triggering and Analysis

- Serial Triggering, Decode, and Analysis Options for I<sub>2</sub>C, SPI, RS-232/422/485/UART, I<sup>2</sup>S/LJ/RJ/TDM, CAN, LIN, and FlexRay

### Additional Application Support

- Power Analysis Option
- HDTV and Custom Video Analysis Option

### Mixed Signal Design and Analysis (MSO4000)

- Parallel Bus Trigger and Analysis
- MagniVu™ 60.6 ps Technology Provides Finer Timing Resolution
- Per-channel Threshold Settings
- Multichannel Setup and Hold Triggering
- Next-generation Digital Waveform Display

### Applications

- Embedded Design and Debug
- Mixed Signal Design and Debug
- Investigation of Transient Phenomena
- Power Measurements
- Video Design and Debug
- Automotive Electronics Design and Debug

## Features & Benefits

### Key Performance Specifications

- 1 GHz, 500 MHz, 350 MHz Bandwidth Models
- 2 and 4 Channel Models
- 16 Digital Channels (MSO4000)
- Sample Rates Up to 5 GS/s on All Channels
- 10 Megasample Record Length on All Channels
- 50,000 wfm/s Maximum Waveform Capture Rate
- Suite of Advanced Triggers

## MSO/DPO4000 Series Digital Phosphor Oscilloscopes

The DPO4000 Series Digital Phosphor Oscilloscopes (DPOs) are the first oscilloscopes to offer usable deep memory on all channels, excellent performance, serial trigger and analysis options, and all in the most compact form factor in their class. The MSO4000 Series Mixed Signal Oscilloscopes (MSOs) provide all the features and benefits of the DPO4000, but add 16 integrated digital channels, enabling you to visualize and correlate analog and digital signals on a single instrument. This integration extends triggering functionality across all 20 channels providing pattern and state triggering ideal for debugging mixed analog and digital designs.

### Designed to Make Your Work Easier

As design complexity increases, you need tools that help you find problems quickly.

### Easy to Setup and Use

The MSO/DPO4000 Series has a large 10.4 inch XGA display, a clean front panel with familiar knobs - all in a package that is only 5.4 in. deep and weighs only 11 lb. With USB plug-and-play operation and PC connectivity, acquiring data and measurements from the instrument is as simple as connecting a USB cable from the oscilloscope to the PC. Provided applications include NI LabVIEW SignalExpress™ Tektronix Edition LE, OpenChoice® Desktop and Microsoft Excel and Word toolbars enabling fast and easy direct communication with your Windows PC. USB and CompactFlash ports on the front panel enable simple transfer of screenshots, instrument settings, and waveform data in the palm of your hand.

When it comes to mixed signal design and debug, you want your instrument to be intuitive so you can start solving problems quickly. The MSO4000 Series drives like an oscilloscope, the tool you already know how to use. You do not have to relearn how to use the instrument every time you turn it on.

### Wave Inspector® Navigation

Imagine trying to efficiently use the Internet if search engines such as Google and Yahoo didn't exist, web browser features such as Favorites and Links didn't exist, or Internet Service Providers like AOL or MSN weren't around. Now you know how most modern oscilloscope users feel when



Wave Inspector® controls.

trying to actually use the long record length in their digital oscilloscope. Record length, one of the key specifications of an oscilloscope, is the number of samples it can digitize and store in a single acquisition. The longer the record length, the longer the time window you can capture with high timing resolution (high sample rate).

The first digital oscilloscopes could capture and store only 500 points, which made it very difficult to acquire all relevant information around the event being investigated. Over the years, oscilloscope manufacturers have provided longer and longer record lengths to meet market demands for long capture windows with high resolution, to the point that most mid-range oscilloscopes either come standard with, or can be optionally upgraded to, multi-megapoint record lengths. These megapoint record lengths often represent thousands of screens worth of signal activity. While standard record lengths have increased greatly over the years and can now satisfy the vast majority of applications in the marketplace, tools for effectively and efficiently viewing, navigating, and analyzing long record length acquisitions have been sorely neglected until now.

## Characteristics

### Vertical System Analog Channels

Characteristic	MSO4032	DPO4034 MSO4034	DPO4054 MSO4054	DPO4104 MSO4104
Input Channels	2	4	4	4
Analog Bandwidth (-3 dB) 5 mV/div - 1 V/div	350 MHz	350 MHz	500 MHz	1 GHz
Calculated Rise Time 5 mV/div (typical)	1 ns	1 ns	700 ps	350 ps
Hardware Bandwidth Limits		20 MHz or 250 MHz		
Input Coupling		AC, DC, GND		
Input Impedance		1 MΩ ±1%, 50 Ω ±1%		
Input Sensitivity, 1 MΩ		1 mV/div to 10 V/div		
Input Sensitivity, 50 Ω		1 mV/div to 1 V/div		
Vertical Resolution		8 bits (11 bits with Hi Res)		
Max Input Voltage, 1 MΩ		250 V <sub>RMS</sub> with peaks ≤ ±400 V		
Max Input Voltage, 50 Ω		5 V <sub>RMS</sub> with peaks < ±20 V		
DC Gain Accuracy		±1.5% with offset set to 0 V		
Offset Range	1 MΩ		50 Ω	
1 mV/div to 50 mV/div	±1 V		±1 V	
50.5 mV/div to 99.5 mV/div	±0.5 V		±0.5 V	
100 mV/div to 500 mV/div	±10 V		±10 V	
505 mV/div to 995 mV/div	±5 V		±5 V	
1 V/div to 5 V/div	±100 V		±5 V	
5.05 V/div to 10 V/div	±50 V		NA	
Channel-to-Channel Isolation	≥100:1 at ≤100 MHz and ≥30:1 at >100 MHz up to the rated bandwidth for any two channels having equal volts/div settings			

### Vertical System Digital Channels

Characteristic	MSO4032	MSO4034	MSO4054	MSO4104
Input Channels		16 Digital (D15 - D0)		
Thresholds		Per-channel Thresholds		
Threshold Selections		TTL, CMOS, ECL, PECL, User Defined		
User-defined Threshold Range		+5 to -2 V		
Maximum Input Voltage		±15 V		
Threshold Accuracy		±(100 mV + 3% of threshold setting)		
Input Dynamic Range		6 V <sub>p-p</sub> centered around the threshold		
Minimum Voltage Swing		500 mV		
Input Impedance		20 kΩ		
Probe Loading		3 pF		
Vertical Resolution		1 bit		

**Horizontal System Analog Channels**

<b>Characteristic</b>	<b>MSO4032</b>	<b>DPO4034 MSO4034</b>	<b>DPO4054 MSO4054</b>	<b>DPO4104 MSO4104</b>
Maximum Sample Rate (all channels)	2.5 GS/s	2.5 GS/s	2.5 GS/s	5 GS/s
Minimum Peak Detect Pulse Width		400 ps		200 ps
Maximum Record Length (all channels)			10 M points	
Maximum Duration at Highest Sample Rate (all channels)	4 ms	4 ms	4 ms	2 ms
Timebase Range		1 ns to 1,000 s		400 ps to 1,000 s
Timebase Delay Time Range			-10 divisions to 5000 s	
Channel-to-Channel Deskew Range			±100 ns	
Timebase Accuracy		±5 ppm over any ≥ 1 ms interval		

**Horizontal System Digital Channels**

<b>Characteristic</b>	<b>MSO4032</b>	<b>MSO4034</b>	<b>MSO4054</b>	<b>MSO4104</b>
Maximum Sample Rate (Main)		500 MS/s (2 ns resolution)		
Maximum Record Length (Main)		10 M points		
Maximum Sample Rate (MagniVu)		16.5 GS/s (60.6 ps resolution)		
Maximum Record Length (MagniVu)		10 k points centered around the trigger		
Minimum Detectable Pulse Width		1.5 ns		
Channel-to-Channel Skew		60 ps typical		

# Data Sheet

## Trigger System

Characteristic	Description
Main Trigger Modes	Auto, Normal, and Single
Trigger Coupling	DC, HF reject (attenuates >50 kHz), LF reject (attenuates <50 kHz), noise reject (reduces sensitivity)
Trigger Holdoff Range	20 ns to 8 s
Trigger Frequency Readout	6-digit hardware counter indicates how often triggerable events are occurring in the user's signal.
Sensitivity	
Internal DC Coupled	0.4 div DC to 50 MHz, increasing to 1 div at rated bandwidth
External (Auxiliary Input)	200 mV from DC to 50 MHz increasing to 500 mV at 250 MHz
Trigger Level Range	
Any Channel	$\pm 8$ divisions from center of screen
External (auxiliary input)	$\pm 8$ V
Trigger Modes	
Edge	Positive or negative slope on any channel or front-panel auxiliary input. Coupling includes DC, HF reject, LF reject, and noise reject.
Sequence (B-trigger)	Trigger Delay by Time - 4 ns to 8 s. Or Trigger Delay by Events - 1 to 9,999,999 events.
Pulse Width	Trigger on width of positive or negative pulses that are $>$ , $<$ , $=$ , or $\neq$ a specified period of time.
Runt	Trigger on a pulse that crosses one threshold but fails to cross a second threshold before crossing the first again.
Logic	Trigger when any logical pattern of channels goes false or stays true for specified period of time. Any input can be used as a clock to look for the pattern on a clock edge. Pattern (AND, OR, NAND, NOR) specified for all analog and digital input channels defined as High, Low, or Don't Care.
Setup and Hold	Trigger on violations of setup time and/or hold time between clock and data present on any of the input channels.
Rise/Fall Time	Trigger on pulse edge rates that are faster or slower than specified. Slope may be positive, negative, or either.
Video	Trigger on line number, all lines, odd, even, or all fields on NTSC, PAL, and SECAM video signals.
Extended Video (optional)	Trigger on 480p/60, 576p/50, 720p/30, 720p/50, 720p/60, 875i/60, 1080i/50, 1080i/60, 1080p/24, 1080p/24sF, 1080p/25, 1080p/30, 1080p/50, 1080p/60, and custom bilevel and trilevel sync video standards.
I <sup>2</sup> C (Optional)	Trigger on Start, Repeated Start, Stop, Missing ACK, Address (7 or 10 bit), Data, or Address and Data on I <sup>2</sup> C buses up to 3.4 Mbps.
SPI (Optional)	Trigger on SS, Idle Time, MOSI, MISO, or MOSI and MISO on SPI buses up to 10.0 Mbps.
CAN (Optional)	Trigger on Start of Frame, Frame Type (data, remote, error, overload), Identifier (standard or extended), Data, Identifier and Data, End of Frame, Missing ACK, or Bit Stuffing Errors on CAN signals up to 1 Mbps. Data can be further specified to trigger on $\leq$ , $<$ , $=$ , $>$ , $\geq$ , or $\neq$ a specific data value. User-adjustable sample point is set to 50% by default.
I <sup>2</sup> S/LJ/RJ/TDM (Optional)	Trigger on Word Select, Frame Sync, or Data. Data can be further specified to trigger on $\leq$ , $<$ , $=$ , $>$ , $\geq$ , $\neq$ a specific data value, or inside or outside of a range.
RS-232/422/485/UART (Optional)	Trigger on Tx start bit, Rx start bit, Tx end of packet, Rx end of packet, Tx data, Rx data, Tx Parity Error, and Rx Parity Error.
LIN (Optional)	Trigger on Sync, Identifier, Data, Identifier and Data, Wakeup Frame, Sleep Frame, or Errors such as Sync, Parity, or Checksum Errors.
FlexRay (Optional)	Trigger on Start of Frame, Type of Frame (Normal, Payload, Null, Sync, Startup), Identifier, Cycle Count, Complete Header Field, Data, Identifier and Data, End of Frame or Errors such as Header CRC, Trailer CRC, Null Frame, Sync Frame, or Startup Frame Errors
Parallel (available on MSO models only)	Trigger on a parallel bus data value.

## Acquisition Modes

Mode	Description
Sample	Acquires sampled values
Peak Detect	Captures glitches as narrow as 200 ps at all sweep speeds
Averaging	From 2 to 512 waveforms included in average
Envelope	Min-max envelope reflecting Peak Detect data over multiple acquisitions
Hi Res	Real-time boxcar averaging reduces random noise and increases vertical resolution
Roll	Scrolls waveforms right to left across screen at sweep speeds slower than or equal to 40 ms/div

## Waveform Measurements

Characteristic	Description
Cursors	Waveform and Screen
Automatic Measurements	29, of which up to eight can be displayed on screen at any one time. Measurements include Period, Frequency, Delay, Rise Time, Fall Time, Positive Duty Cycle, Negative Duty Cycle, Positive Pulse Width, Negative Pulse Width, Burst Width, Phase, Positive Overshoot, Negative Overshoot, Peak to Peak, Amplitude, High, Low, Max, Min, Mean, Cycle Mean, RMS, Cycle RMS, Positive Pulse Count, Negative Pulse Count, Rising Edge Count, Falling Edge Count, Area, and Cycle Area.
Measurement Statistics	Mean, Min, Max, Standard Deviation
Reference Levels	User-definable reference levels for automatic measurements can be specified in either percent or units
Gating	Isolate the specific occurrence within an acquisition to take measurements, using either the screen or waveform cursors

**Power Measurements (optional)**

Characteristic	Description
Power Quality Measurements	$V_{RMS}$ , $V_{Crest\ Factor}$ , Frequency, $I_{RMS}$ , $I_{Crest\ Factor}$ , True Power, Apparent Power, Reactive Power, Power Factor, Phase Angle
Switching Loss Measurements	Power Loss: $T_{on}$ , $T_{off}$ , Conduction, Total Energy Loss: $T_{on}$ , $T_{off}$ , Conduction, Total
Harmonics	THD-F, THD-R, RMS measurements Graphical and table displays of harmonics Test to IEC61000-3-2 Class A and MIL-STD-1399
Ripple Measurements	$V_{ripple}$ and $I_{ripple}$
Modulation Analysis	Graphical display of +Pulse Width, -Pulse Width, Period, Frequency, +Duty Cycle, and -Duty Cycle modulation types
Safe Operating Area	Graphical display and mask testing of switching device safe operating area measurements
dV/dt and dI/dt Measurements	Cursor measurements of slew rate

**Waveform Math**

Characteristic	Description
Arithmetic	Add, subtract, multiply, and divide waveforms
Math Functions	Integrate, Differentiate, FFT
FFT	Spectral magnitude. Set FFT Vertical Scale to Linear RMS or dBV RMS, and FFT Window to Rectangular, Hamming, Hanning, or Blackman-Harris.
Advanced Math	Define extensive algebraic expressions including analog waveforms, math functions, scalars, up to two user-adjustable variables, and results of parametric measurements (both static and trend plots) e.g., (Intg (Ch1-Mean(Ch1)) × 1.414 × VAR1).

**Software**

Software	Description
NI LabVIEW SignalExpress Tektronix Edition LE	A fully interactive measurement software environment optimized for the MSO/DPO4000 Series, enables you to instantly acquire, generate, analyze, compare, import, and save measurement data and signals using an intuitive drag-and-drop user interface that does not require any programming. Standard MSO/DPO4000 Series support for acquiring, controlling, viewing, and exporting your live signal data is permanently available through the software. The full version (SIGEXPTE) adds additional signal processing, advanced analysis, mixed signal, sweeping, limit testing, and user-defined step capabilities and is available for a 30-day trial period standard with each instrument.
OpenChoice® Desktop	Enables fast and easy communication between a Windows PC and the MSO/DPO4000 Series, using USB or LAN. Transfer and save settings, waveforms, measurements, and screen images.
IVI Driver	Provides a standard instrument programming interface for common applications such as LabVIEW, LabWindows/CVI, Microsoft .NET and MATLAB.

**Display Characteristics**

Characteristic	Description
Display Type	10.4 in. (264 mm) liquid-crystal TFT color display
Display Resolution	1,024 horizontal × 768 vertical pixels (XGA)
Waveform Styles	Vectors, Dots, Variable Persistence, Infinite Persistence
Graticules	Full, Grid, Cross Hair, Frame, IRE, and mV
Format	YT and simultaneous XY/YT
Waveform Capture Rate	Up to 50,000 wfms/sec

**Input/Output Ports**

Port	Description
CompactFlash Drive	Front-panel access (Type 1)
USB 2.0 Full-speed Host Port	Supports USB mass storage devices, printers and keyboard. Two ports available on rear panel and one on front panel.
USB 2.0 High-speed Device Port	Rear-panel connector allows for control of oscilloscope through USBTMC or GPIB with a TEK-USB-488 or connection to a PictBridge printer.
LAN Port	RJ-45 connector, supports 10/100Base-T
XGA Video Port	DB-15 female connector, connect to show the oscilloscope display on an external monitor or projector
Auxiliary Input	Front-panel BNC connector. Input Impedance 1 MΩ. Max input 250 V <sub>RMS</sub> with peaks ±400 V.
Probe Compensator Output	Front-panel pins Amplitude 2.5 V Frequency 1 kHz
Trigger Out	Rear-panel BNC connector, provides a positive polarity pulse when the oscilloscope triggers
Kensington Lock	Rear-panel security slot connects to standard Kensington lock

**Power Source**

Characteristic	Description
Power Source Voltage	100 to 240 V ±10%
Power Source Frequency	47 to 66 Hz (90 to 264 V) 360 to 440 Hz (100 to 132 V)
Power Consumption	250 W maximum

**Physical Characteristics**

Dimensions	mm	in.
Height	229	9.0
Width	439	17.3
Depth	137	5.4
Weight	kg	lb.
Net	5	11
Shipping	9.5	22
Rackmount		5U
Configuration		
Cooling Clearance	2 in. (51 mm) required on left side and rear of instrument	

# Data Sheet

## General Characteristics

Characteristic	Description
<b>Environmental</b>	
Temperature	
Operating	0 °C to +50 °C
Nonoperating	-20 °C to +60 °C
Humidity	
Operating	High: 40 °C to 50 °C, 10% to 60% Relative Humidity Low: 0 °C to 40 °C, 10% to 90% Relative Humidity
Nonoperating	High: 40 °C to 60 °C, 5% to 60% Relative Humidity Low: 0 °C to 40 °C, 5% to 90% Relative Humidity
Altitude	
Operating	3,000 meters (9,843 feet)
Nonoperating	12,000 meters (39,370 feet)
Random Vibration	
Operating	0.31 G <sub>RMS</sub> from 5 to 500 Hz, 10 minutes each axis, 3 axes, 30 minutes total
Nonoperating	2.46 G <sub>RMS</sub> from 5 to 500 Hz, 10 minutes each axis, 3 axes, 30 minutes total
<b>Regulatory</b>	
Electromagnetic Compatibility	89/336/EEC
Safety	UL61010-1, Second Edition; CSA61010-1 Second Edition, EN61010-1:2001; IEC 61010-1:2001

## Ordering Information

### MSO/DPO4000 Family

Model	Description
<b>DPO4000 Models</b>	
DPO4034	350 MHz, 2.5 GS/s, 10 M record length, 4-channel digital phosphor oscilloscope
DPO4054	500 MHz, 2.5 GS/s, 10 M record length, 4-channel digital phosphor oscilloscope
DPO4104	1 GHz, 5 GS/s, 10 M record length, 4-channel digital phosphor oscilloscope
<b>MSO4000 Models</b>	
MSO4032	350 MHz, 2.5 GS/s, 10 M record length, 2+16 channel mixed-signal oscilloscope
MSO4034	350 MHz, 2.5 GS/s, 10 M record length, 4+16 channel mixed-signal oscilloscope
MSO4054	500 MHz, 2.5 GS/s, 10 M record length, 4+16 channel mixed-signal oscilloscope
MSO4104	1 GHz, 5 GS/s, 10 M record length, 4+16 channel mixed-signal oscilloscope

All models include: One P6139A 500 MHz, 10x Passive Probe per Analog Channel, Front Cover (200-4908-00), CompactFlash Memory Card; ≥32 MB (156-9413-00), User Manual (071-2121-xx), Documentation CD (063-3903-00), OpenChoice® Desktop Software, NI LabVIEW SignalExpress™ Tektronix Edition LE Software, Calibration certificates document measurement traceability to National Metrology

Institute(s) - the Quality System this product is manufactured in is ISO9001 registered, power cord, accessory bag (016-1967-00) and a three-year warranty. Please specify power plug and manual version when ordering. MSO models also include one P6516 16-channel logic probe and a logic probe accessory kit (020-2662-00).

## Application Modules

Module	Description
DPO4EMBD	Embedded Serial Triggering and Analysis Module. Enables triggering on packet level information on I <sup>2</sup> C and SPI buses as well as analytical tools such as digital views of the signal, bus views, packet decoding, search tools, and packet decode tables with time stamp information.
DPO4COMP	Computer Serial Triggering and Analysis Module. Enables triggering on packet level information on RS-232/422/485/UART buses as well as analytical tools such as digital views of the signal, bus views, packet decoding, search tools, and packet decode tables with time stamp information.
DPO4AUDIO	Audio Serial Triggering and Analysis Module. Enables triggering on packet level information on I <sup>2</sup> S, LJ, RJ, and TDM audio buses as well as analytical tools such as digital views of the signal, bus views, packet decoding, search tools, and packet decode tables with time stamp information.
DPO4AUTO	Automotive Serial Triggering and Analysis Module. Enables triggering on packet level information on CAN and LIN buses as well as analytical tools such as digital views of the signal, bus views, packet decoding, search tools, and packet decode tables with time stamp information.
DPO4AUTOMAX	Extended Automotive Serial Triggering and Analysis Module. Enables triggering on packet level information on CAN, LIN and FlexRay buses as well as analytical tools such as digital views of the signal, bus views, packet decoding, search tools, packet decode tables with time stamp information, and eye-diagram analysis software.
DPO4PWR	Power Analysis Application Module. Enables quick and accurate analysis of power quality, switching loss, harmonics, safe operating area (SOA), modulation, ripple, and slew rate (dI/dt, dV/dt).
DPO4VID	HDTV and Custom (nonstandard) Video Triggering Module.

## Instrument Options

### Power Plug Options

Option	Description
Opt. A0	North America
Opt. A1	Universal Euro
Opt. A2	United Kingdom
Opt. A3	Australia
Opt. A5	Switzerland
Opt. A6	Japan
Opt. A10	China
Opt. A11	India
Opt. A99	No power cord or AC adapter

**Language Options\*1**

<b>Option</b>	<b>Description</b>
Opt. L0	English manual
Opt. L1	French manual
Opt. L2	Italian manual
Opt. L3	German manual
Opt. L4	Spanish manual
Opt. L5	Japanese manual
Opt. L6	Portuguese manual
Opt. L7	Simplified Chinese manual
Opt. L8	Standard Chinese manual
Opt. L9	Korean manual
Opt. L10	Russian manual
Opt. L99	No manual

\*1 Language options include a translated front-panel overlay for the selected language(s).

**Service Options\*2**

<b>Option</b>	<b>Description</b>
Opt. C3	Calibration Service 3 years
Opt. C5	Calibration Service 5 years
Opt. CA1	Provides a single calibration event, or coverage for the designated calibration interval, whichever comes first.
Opt. D1	Calibration Data Report
Opt. D3	Calibration Data Report 3 years (with Opt. C3)
Opt. D5	Calibration Data Report 5 Years (with Opt. C5)
Opt. R5	Repair Service 5 years (including warranty)

\*2 Probes and accessories are not covered by the oscilloscope warranty and service offerings. Refer to the datasheet of each probe and accessory model for its unique warranty and calibration terms.

**Recommended Probes**

<b>Probe</b>	<b>Description</b>
TAP1500	1.5 GHz TekVPI™ active probe
TAP1500X2	Bundle of Two 1.5 GHz Active Probes, single-ended with TekVPI Interface, Certificate of traceable calibration standard
TDP0500	500 MHz TekVPI 42 V differential probe
TDP1000	1 GHz TekVPI 42 V differential probe
TCP0030	120 MHz TekVPI 30 Ampere AC/DC current probe
TCP0150	20 MHz TekVPI 150 Ampere AC/DC current probe
TCPA300/400*3	Current measurement systems
P5200	1.3 kV, 25 MHz high-voltage differential probe
P5205*3	1.3 kV, 100 MHz high-voltage differential probe
P5210*3	5.6 kV, 50 MHz high-voltage differential probe
P5100	2.5 kV, 100X high-voltage passive probe
ADA400A*3	100X, 10X, 1X, 0.1X high-gain differential amplifier
NEX-HD2HEADER	Mictor connector breakout to 0.1 in. header pins
DPO4PWRBND Power Solution Bundle	Includes P5205 and TDP0500 differential voltage probes, TCP0030 current probe, TPA-BNC adapter, deskew pulse generator (TEK-DPG), deskew fixture, and power analysis module (DPO4PWR) in a hard-sided carrying case. Bundle discount reflected in price.

\*3 Requires TekVPI™ to TekProbe BNC adapter (TPA-BNC).

**Recommended Accessories**

<b>Accessory</b>	<b>Description</b>
071-1844-XX	Service Manual (English only)
SIGEXPTE	NI LabVIEW SignalExpress™ Tektronix Edition Software (Full Version)
FPGAView-xx	MSO Support for Altera and Xilinx FPGAs
TPA-BNC	TekVPI to TekProbe BNC Adapter
TEK-USB-488	GPIB to USB Adapter
TLAHR4 with (2) 196-3476-01	High-impedance Adapter and Leadsets for P6516 MSO Probe
119-6827-00	CompactFlash to USB Memory Card Reader
ACD4000	Soft Transit Case
HCTEK4321	Hard Transit Case (Requires ACD4000)
RM4000	Rackmount Kit
AMT75*3	1 GHz, 75 Ω Adapter
TEK-DPG	Deskew Pulse Generator
067-1686-00	Deskew Fixture

\*3 Requires TekVPI™ to TekProbe BNC adapter (TPA-BNC).

**Warranty**

Three-year warranty covering all parts and labor, excluding probes.



Product(s) are manufactured in ISO registered facilities.



Product(s) complies with IEEE Standard 488.1-1987, RS-232-C, and with Tektronix Standard Codes and Formats.