

► Tenney

Thermal Shock Chambers

Tenney Thermal Shock Chambers

The Tenney T-Shock Junior is a bench-top thermal shock chamber with a 1/4 cubic foot carriage capacity. It's designed to accommodate pilot runs and smaller production quantities of sophisticated, discrete components.

The T-Shock Junior provide an cost-effective alternative to larger capacity units.

► Features

- Vapor-tight interior liners made of 100% continuously welded stainless steel
- Control system provides fully automatic, PID, chamber control through a user-friendly alpha-numeric display
- Available in horizontal or vertical configurations
- Available in two or three zone operations
- Carriage transport is automatically positioned and includes a large wire mesh stainless steel product basket



Carriage Capacity		Product Load	Refrigeration	Heat	Dimensions W x H x D inches (cm)		Model	Wt lbs.
Ft³	W x H x D inches (cm)	LBS.	HP	KW	Horizontal Model	Vertical Model		
TSJR Model (Air Cooled)								
.25	10.5 x 6 x 6.125 (26.7 x 15.2 x 15.6)	3	½ + ½ + LN2	2.5/5	63 x 41 x 22 (160 x 104.1 x 55.9)	N/A	TSJR	700
TS2 Models - Two Zone: Hot/Cold (Water Cooled)								
2	15 x 15 x 15 (38.1 x 38.1 x 38.1)	15	4 + LN2	9/2	88 x 57 x 74 (223.5 x 144.8 x 188)	89 x 72 x 58 (226.1 x 182.9 x 147.3)	TS2.02.04B	3700
2		11	10				TS2.02.10	4000
8	25 x 23 x 25 (V) (63.5 x 58.4 x 63.5)	35	6 + LN2	21/4	99 x 75 x 88 (251.5 x 190.5 x 223.5)	97 x 89 x 75 (246.4 x 226.1 x 190.5)	TS2.08.06B	4200
8	or 23 x 25 x 25 (H) (58.4 x 63.5 x 63.5)	35	30				TS2.08.30	4700
TSD Models - Dual Load: Hot/Cold/Hot (Water Cooled)								
2	15 x 15 x 15 (38.1 x 38.1 x 38.1)	28	4 + LN2	18/2	129 x 88 x 53 (327.7 x 223.5 x 134.6)	88 x 57 x 74 (223.5 x 144.8 x 188)	TSD.02.04B	4200
2		18	10				TSD.02.10	4500
8	25 x 23 x 25 (V) (63.5 x 58.4 x 63.5)	60	6 + LN2	42/4	156 x 88 x 72 (396.2 x 223.5 x 182.9)	99 x 75 x 88 (251.5 x 190.5 x 223.5)	TSD.08.06B	4700
8	or 23 x 25 x 25 (H) (58.4 x 63.5 x 63.5)	56	30				TSD.08.30	5200

► Thermal Shock Chambers Features

- Vapor-tight interior liners made of 100% continuously welded stainless steel
- Control system provides fully automatic, PID, chamber control through a user-friendly alpha-numeric display
- Available in horizontal or vertical configurations and two or three zone operation
- Carriage transport is automatically controlled and positioned and includes a large wire mesh stainless steel product basket

Specifications & Product Information is subject to change without notice.
Images for reference only. Options and accessories may not be included with all models.



Gruenberg, Blue M, Tenney

Mailing Address: P.O. Box 150 | White Deer, PA 17887-0150 | USA |

Phone: (570) 538-7200 | Fax: (570) 538-7380

Physical Address: 2821 Old Route 15 | New Columbia, PA 17856-9396

TPSinfo@tps.spx.com